15.6" Fanless All-in-one PC | TP-5040-16

Widescreen Industrial Computer





Features

- 15.6" True Flat Touchscreen with LCD Display
- Intel Skylake Core i3/i5 CPU
- Fanless and Low Power Consumption
- Aluminum Die-Cast Housing
- Several I/Os and HDD Bay
- Optional Webcam, WLAN, & BT 4.0

Technical Specifications

System

Processor	Intel Skylake Core i3/i5 CPU
CPU Performance	2.3GHz, 2.4GHz
Video / Graphics Card	Intel HD Graphics
Storage	2.5" Slim HDD Bay
Memory (RAM)	2GB, 4GB, 8GB
Display	
Screen Size	15.6"
Type of Backlight	LED
Screen Resolution	1366 x 768
Display Ratio	16:9
Contrast Ratio	1000:1
Brightness	250 nits
Touch Screen	
Hardness	\geq 6H (P-Cap) / \geq 3H (Resistive)
Lifetime Usage	30,000 hrs
Interface	USB (internal) Acetic Acid, Acetone, Alcohol, Ammonia,
Approved	CIDEX, Ethanol, Gasoline, Glycerine,
Cleaning	Incidin, Isopropanol/Propanol, Kerosene,
Agents	Lanoline, Methanol, Paraffin Oil, Salt
	Solution, Toluene, Vaseline, Windex
I/O Ports	
USB 2.0	2 x USB 2.0
USB 3.0	4 x USB 3.0
	1
Video	1x VGA, 1x DVI
Ethernet	2 x RJ45 GbE
Ethernet Other Ports	2 x RJ45 GbE Display Port (Optional)
Ethernet Other Ports Operating Syster	2 x RJ45 GbE Display Port (Optional) n
Ethernet Other Ports Operating Syster Operating	2 x RJ45 GbE Display Port (Optional) n Linux, Windows 10 Pro, Windows 10 IoT,
Ethernet Other Ports Operating Syster Operating System	2 x RJ45 GbE Display Port (Optional) n
Ethernet Other Ports Operating Syster Operating System Power	2 x RJ45 GbE Display Port (Optional) n Linux, Windows 10 Pro, Windows 10 IoT,
Ethernet Other Ports Operating Syster Operating System	2 x RJ45 GbE Display Port (Optional) n Linux, Windows 10 Pro, Windows 10 IoT, Windows 8.1 Embedded
Ethernet Other Ports Operating System Operating System Power DC Input	2 x RJ45 GbE Display Port (Optional) n Linux, Windows 10 Pro, Windows 10 IoT, Windows 8.1 Embedded 12~48V
Ethernet Other Ports Operating System Operating System Power DC Input Power Adapter	2 x RJ45 GbE Display Port (Optional) n Linux, Windows 10 Pro, Windows 10 IoT, Windows 8.1 Embedded 12~48V


D° to 35°C (32° to 95°F) 20° to 60°C (-4° to 140°F) 20% to 85% (non-condensing) hermal Solution Passive - Fanless ht 4.5000 396 x 48 x 245mm (15.59 x 1.89 x 9.65in) P65 Protected
20% to 85% (non-condensing) hermal Solution Passive - Fanless ht 4.5000 396 x 48 x 245mm (15.59 x 1.89 x 9.65in)
hermal Solution Passive - Fanless ht 4.5000 396 x 48 x 245mm (15.59 x 1.89 x 9.65in)
Passive - Fanless ht 4.5000 396 x 48 x 245mm (15.59 x 1.89 x 9.65in)
ht 4.5000 396 x 48 x 245mm (15.59 x 1.89 x 9.65in)
4.5000 396 x 48 x 245mm (15.59 x 1.89 x 9.65in)
396 x 48 x 245mm (15.59 x 1.89 x 9.65in)
9.65in)
P65 Protected
P65 Protected
Black, White
Panel Mount, VESA Mount, Wall Mount
VESA 75
Acetic Acid (low concentration), Ammonium Nitrate (low concentration), Benzine, Citric Acid (low concentration), Ethanol, Ethylene Glycol Solution (1:1 with water), Hexane, Hydrochloric Acid (low concentration), Iron Chloride Solution, Isooctane, Isopropyl Alcohol, Nitric Acid (low concentration), Paraffin, Perhydrol (30% in water), Phosphoric Acid (low concentration), Propane, Silicone Oil, Sodium Carbonate (low concentration), Sodium Chloride Solution, Sodium Nitrate (low concentration), Sulfuric Acid (low concentration), Friethylene Glycol
Dptional 802.11 b/g/n WLAN card +
Bluetooth 4.0
Optional 2D Scanner
Optional RFID Module Optional MSR

15.6" Fanless All-in-one PC | TP-5040-16

Widescreen Industrial Computer

GLACIER





866-724-6257 x 6 - sales@glaciercomputer.com