





UX10 FULLY RUGGED

- 10th Generation Intel® Core™ i7/i5 Processor
- 10.1" FHD LumiBond® 2.0 Display with Getac Sunlight Readable Technology (1,000 nits) and Capacitive Touchscreen
- Enhanced Enterprise Security with Optional Intel vPro™, Windows Hello Face-authentication Camera and Multi-factor **Authentication Options**
- Detachable Keyboard and Multifunctional Hard Handle for On-the-job Flexibility
- Multiple Configurable Options to Fit Diverse **Usage Scenarios**















Specifications

Operating System

Windows 10 Pro

Mobile Computing Platform

Platform Options:

Intel® Core™ i7 Technology Intel® Core™ i7-10510U Processor 1.80 GHz 8MB Intel® Smart Cache

Intel® Core™ i7 vPro™ Technology Intel® Core™ i7-10610U Processor 1.80 GHz vPro 8MB Intel® Smart Cache

Intel® Core™ i5 Technology Intel® Core™ i5-10210U Processor 1.60 GHz

6 MB Smart Cache

Intel® Core™ i5 vPro™ Technology Intel® Core™ i5-10310U Processor 1.70 GHz vPro 6MB Intel® Smart Cache

VGA Controller

Intel® UHD Graphics

Display

10.1" IPS TFT LCD FHD (1920 x 1200) 1000 nits LumiBond® display with Getac sunlight readable technology

Capacitive multi-touch screen **Storage & Memory**

8GB DDR4

Optional: 16GB / 32GB DDR4

256GB PCIe NVMe SSD Optional: 512GB / 1TB PCIe NVMe SSD

6 tablet buttons (Windows, Power, Function Key, Camera Capture/ Barcode Reader Trigger, Volume Up, Volume Down)

Pointing Device

- Touchscreen
 Capacitive multi-touch screen
- Optional: Dual mode touchscreen (multi-touch and digitizer)

Expansion Slot

- Optional (top side): 1D/2D imager barcode reader', or serial port, or MicroSD slot, or USB 3.0 Type-A port, or USB 3.1 Gen 1 Type-C port, or LAN port (RJ-45), or VGA port", or HF RFID reader.
- Optional (right side): fingerprint reader, or serial port+LAN port (RJ-45), or HF RFID reader
- Optional (back side): smart card reader, or bridge battery, or bridge battery+smart card reader 1/0

Interface

FHD webcam x 1 or Optional Windows Hello face-authentication camera (front-facing) x 1 8M pixels auto focus rear camera x 1 Headphone out / mic-in combo x 1

DC in Jack x 1 USB 3.1 Gen 2 Type-A x 1

HDMI x 1

Docking connector x 1
Optional: RF antenna pass-through for GPS,

WLAN and WWAN

Communication Interface

Optional: 10/100/1000 base-T Ethernet Intel® Wi-Fi 6 AX200, 802.11ax

Bluetooth (v5.1)vii Optional: Dedicated GPSiii Optional: 4G LTE mobile broadband with

integrated GPS **Security Feature**

Optional: Intel® vPro™ Technology

TPM 2.0 Optional: HF RFID reader^{i,ii}

Optional: Fingerprint scanner

Optional: smart card reader*

Kensington lock

Power

AC adapter (65W, 100-240VAC, 50 / 60Hz) Li-lon smart battery (11.1V, typical 4200mAh; min.4080mAh) x 1

Optional: High capacity battery (10.8V, 9240mAh)

Optional: Bridge battery' **Dimension (W x D x H) & Weight** 194.5

10.89" x 7.65" x 0.92", 2.68 lbs^{vii}

Rugged Feature
MIL-STD-810H certified and IP65 certified MIL-STD-461G certified

Optional: ANSI/UL 121201, CSA C22.2 NO. 213 Optional: Salt fog certified

6 feet drop resistanti^{x,x} e-Mark certified for vehicle usage

Environmental Specification

Temperature^x

- Operating: -29°C to 63°C / -20°F to 145°F Storage: -51°C to 71°C / -60°F to 160°F
- 95% RH , non-condensing

Software

Getac Utility Getac Camera Getac Geolocation Getac Barcode Manager Optional Absolute Persistence

Accessories

Carry bag
Multi-bay charger (Dual Bay)
Multi-Bay charger (Eight-Bay)
Vehicle adapter (120W, 11-32VDC)
AC adapter (65W, 100-240VAC)
Office dock AC adapter (90W, 100-240VAC)
MIL-STD-461 certified AC adapter (90W, 100-240VAC) Digitizer pen Capacitive stylus (Hard-tip) Protection film Tablet folio case Hand strap Shoulder harness (4-point; handsfree) Shoulder strap (2-point)
Standard battery (11.1V, typical 4200mAh; min. High capacity battery (10.8V, 9240 mAh) Detachable keyboard

Bumper-to-Bumper warranty

Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment

That is why Getac has introduced accidental damage as standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs.

Bumper-to-Bumper is your hassle-free guarantee. That means you can depend on us to have your unit back in service within days.

Standard

3 years Bumper-to-Bumper

- 13.56MHz Contactless HF RFID reader (ISO 15693, 14443 A/B, Mifare and FeliCa™
- compliant).

 1D/2D imager barcode reader, HF RFID reader, serial port, LAN port (RJ45), USB 3.0 port, USB 3.1 Gen 1 Type-C port, MicroSD slot and VGA port are mutually exclusive options. Supports GPS and Glonass.

 Fingerprint scanner, HF RFID reader and serial port+LAN port (RJ45) are mutually exclusive options.
- Smart card reader, bridge battery and bridge battery+smart card reader are mutually
- exclusive options.

 Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
- operating in the area.

 vii Weight and dimensions vary from configurations and optional accessories.

 viii MIL-STD-461G 90W AC adapter sold separately.

 ix Drop test results vary from configurations and optional accessories.


 x Tested by a national independent third party test lab following MIL-STD-810H.

Fully Rugged Tablet



Docking Solutions

	Vehicle Dock	Office Dock
Serial Port	1	1
VGA		1
Microphone		1
Audio Output		1
DC in Jack	1	1
USB	USB 3.0 x2 USB 2.0 x2	USB 3.0 x2 USB 2.0 x2
LAN	1	1
HDMI		1
RF Antenna Connector	3 (WWAN, WLAN, GPS)	
Kensington Lock	1	1



Glacier Computer

603.882.1560 Ext. 6 sales@glaciercomputer.com www.glaciercomputer.com