



Dro

# ZX70 December of the second se

- Qualcomm<sup>®</sup> Snapdragon<sup>™</sup> 660, Octa-core Processor
- Verified as Android Enterprise Recommended<sup>i</sup>
- 7" LumiBond<sup>®</sup> Display with Getac Sunlight Readable Technology and Glove-enabled Capacitive Touchscreen
- 6 Feet Drop , MIL-STD-810H and IP67 Certified
- Optional Barcode Reader and RFID Reader
- High Sensitivity GPS



## **Rugged Mobile Computing Solutions**

# **Specifications**

### **Operating System** Android<sup>™</sup> 9.0

Mobile Computing Platform Qualcomm<sup>®</sup> Snapdragon<sup>™</sup> 660, Octa-core 1.95 GHz, burst up to 2.2 GHz

**VGA** Controller Qualcomm<sup>®</sup> Adreno<sup>™</sup> 512 GPU

Display 7" IPS TFT LCD HD (1280 x 720) Protection film LumiBond® display with Getac sunlight readable technology

### Capacitive multi-touch screen

**Storage & Memory** 4GB LPDDR4

### 64GB eMMC Keyboard

Power button 3 tablet programmable buttons

**Pointing Device** Touchscreen Capacitive multi-touch screen

**Expansion Slot** MicroSD x1

### **I/O Interface**

8M pixels webcam x 1 12M pixels auto focus rear camera x 1 DC in Jack x 1 USB 2.0 (Host) x 1 MicroUSB 2.0 (Client) x 1 Docking Connector (Pogo / JAE) x 1 MicroSD x 1 Optional: RF antenna pass-through for GPS and WWAN

### **Communication Interface**

Wi-Fi 802.11ac Bluetooth (v5.0)<sup>i</sup> Dedicated GPS Optional: 4G LTE mobile broadband

### **Security Feature**

Optional: Contactless HF RFID / NFC combo reader<sup>iii,</sup> Optional: Barcode reader

### Power

AC adapter (25W, 100-240VAC, 50 / 60Hz) Li-Ion battery (3.8V, typical 8480mAh; min. 8220mAh)

Dimension (W x D x H) & Weight 218 x 142 x 27 mm (8.58" x 5.6" x 1.08") 762 g (1.68 lbs)<sup>ii</sup>

### **Rugged Feature**

MIL-STD-810H certified IP67 certified Vibration & 6 feet drop resistant Optional: ANSI / UL 121201, CSA C22.2 NO. 213

### **Environmental Specification** Temperature<sup>v</sup>

Operating: -21°C to 60°C / -6°F to 140°F Storage: -40°C to 71°C / -40°F to 160°F Storage:

# Humidity: - 95% RH , non-condensing

### **Pre-installed Software** Getac File Brower

Getac Camera Getac Input Method DeployeXpress Client Getac Settings and Google Applications (Search, Chrome, Gmail, Maps, YouTube, Play, Drive, Play Music, Play Movies, Duo and Photos) Accessories

AC Adapter (25W; 12V/2A, 100-240VAC; 50 / 60 Hz) Capacitive Stylus Pen holder

Wrist Strap Optional:

Carry Bag AC Adapter (25W; 12V/2A, 100-240VAC; 50 / 60 Hz) Office Dock AC Adapter (60W, 110-240VAC) Vehicle Adapter (40W 11-16V, 20-32VDC) Capacitive Stylus Protection Film Shoulder Strap (2-point) Wrist Strap Rotating Hand Strap with Kickstand and Stylus

Holder USB to RS232 Converter Cable

Docking Connector to HDMI Converter Cable Vehicle Dock Office Dock

### Bumper-to-Bumper Warranty

Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime.

That is why Getac has introduced accidental damage as standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs. Bumper-to-Bumper is your hassle-free guarantee. That means you can depend on us to have your unit back in service within days. Standard

3 years Bumper-to-Bumper

- Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
- 13.56MHz Contactless HF RFID/NFC reader (ISO 15693, 14443 A/B, Mifare and FeliCa™ ii.
- (ISO 15693, 14443 Ave, Millare and relieve compliant). HF RFID / NFC combo reader applies to US & EU. Weight and dimensions vary from configurations and optional accessories. Tested by a national independent third party test lab following MIL-STD-810H. iii iv
- v

# **ZX7**0 Fully Rugged **Tablet**



### **Docking Solutions**

	Getac-made Vehicle Dock (JAE)	Havis Vehicle Dock (JAE)	Gamber-Johnson Charging Cradle (Pogo)	Havis Vehicle Dock (Pogo)	Office Dock (JAE)	Office Dock (Pogo)
Serial Port	1	1		1		
Speaker	1					
Audio Output	1	1		1	1	1
DC in Jack	1	1	1	1	1	1
USB	USB Host x 2	USB2.0 x 2		USB2.0 x 2	USB Host x 2 MicroUSB Client x 1	USB Host x 2
LAN	1	1		1	1	1
HDMI	1	1			1	
RF antenna connector	(WWAN, GPS)	(WWVAN, GPS)		(VVVVAN, GPS)		



### **Glacier Computer**

603.882.1560 Ext. 6 sales@glaciercomputer.com www.glaciercomputer.com