




K120 FULLY Rugged tablet

- 11th Generation Intel[®] Core™ i7 / i5 vPro™ Processor
- 12.5" FHD LumiBond[®] display with Getac sunlight readable technology (1,200 nits) and capacitive touchscreen
- Enhanced enterprise security with optional Intel vPro, Windows Hello face-authentication camera, and multi-factor authentication options
- Multi-mode usage streamlined by extensive accessory selections
- LifeSupport[™] battery swappable technology
- Thunderbolt[™] 4 brings lightning speed and performance







GLACIER COMPUTER

603.882.1560. ext 6 sales@glaciercomputer.com https://glaciercomputer.com

SPECIFICATIONS

| Generation | G2 | | | |
|---------------------------|--|--|--|--|
| Operating System | Windows 10 Pro | | | |
| | Windows 11 Pro | | | |
| Mobile Computing Platform | Intel [®] Core™ i5-1135G7 Processor | | | |
| | Max. 4.2GHz with Intel [®] Turbo Boost Technology | | | |
| | - 8MB Intel [®] Smart Cache | | | |
| | Platform options: | | | |
| | Intel [®] Core™ i5-1145G7 vPro™ Processor | | | |
| | Max. 4.4GHz with Intel [®] Turbo Boost Technology | | | |
| | - 8MB Intel [®] Smart Cache | | | |
| | Intel [®] Core™ i7-1165G7 Processor | | | |
| | Max. 4.7GHz with Intel [®] Turbo Boost Technology | | | |
| | - 12MB Intel [®] Smart Cache | | | |
| | Intel [®] Core™ i7-1185G7 vPro™ Processor | | | |
| | Max. 4.8GHz with Intel [®] Turbo Boost Technology | | | |
| | - 12MB Intel [®] Smart Cache | | | |
| VGA Controller | Intel [®] Iris [®] X ^e Graphics ^{xv} | | | |
| Display | 12.5" IPS TFT LCD FHD (1920 x 1080) | | | |
| | Protection film | | | |
| | 1,200 nits LumiBond [®] display with Getac sunlight readable | | | |
| | technology | | | |
| | Capacitive multi-touch screen | | | |
| Storage & Memory | 16GB DDR4 | | | |
| Storage & Memory | Optional: 32GB / 64GB DDR4 | | | |
| | 256GB PCIe NVMe SSD | | | |
| | Optional: 512GB / 1TB / 2TB PCIe NVMe SSD | | | |
| Keyboard | Power button | | | |
| Reyboard | 5 tablet programmable buttons | | | |
| Pointing Device | Touchscreen | | | |
| | - Capacitive multi-touch screen | | | |
| | | | | |



| Expansion Slots | Optional: 1D/2D imager barcode reader Optional: Serial port (9-pin; D-sub), or USB 2.0 port | | |
|-------------------------|--|--|--|
| /O Interfaces | Tablet | | |
| | FHD webcam x 1 ⁺ | | |
| | 8M pixels auto focus rear camera x 1 | | |
| | Audio in/out combo x 1 | | |
| | DC in Jack x 1 | | |
| | USB 3.2 Gen 2 Type-A x 1 | | |
| | Thunderbolt™ 4 Type-C x 1 | | |
| | LAN (RJ-45) x 1 | | |
| | HDMI 2.0 x 1 | | |
| | Docking connector x 2 | | |
| | Optional: SIM card slot x 1 (Micro-SIM, 3FF) | | |
| | Optional: Windows Hello face-authentication camera (front- facing) x 1 ⁱ | | |
| | Optional: RF antenna pass-through for GPS, WWAN and | | |
| | WLAN | | |
| | Optional keyboard dock: | | |
| | DC in Jack x 1 | | |
| | USB 3.2 Gen 1 Type-A x 3 | | |
| | LAN (RJ45) x 1 | | |
| | HDMI 2.0 x 1 | | |
| | Display port 1.2 x 1 | | |
| | Serial port (9-pin; D-sub) x 1 | | |
| | Optional: RF antenna pass-through for GPS, WWAN and WLAN | | |
| Communication Interface | 10/100/1000 base-T Ethernet | | |
| | Intel [®] Wi-Fi 6 AX201, 802.11ax | | |
| | Bluetooth (v5.2) " | | |
| | Optional: Dedicated GPS ^{III} | | |
| | Optional: 4G LTE mobile broadband with integrated GPS ^{iii, iv} | | |
| Security Features | TPM 2.0 | | |
| security reatures | Kensington lock | | |
| | Optional: Intel [®] vPro™ Technology | | |
| | Optional: Smart card reader or HF RFID reader ^{v, vi} or | | |
| | Fingerprint reader ^{vii} | | |
| Power | AC adapter (90W, 100-240VAC, 50/60Hz) | | |
| Ower | Li-ion battery (11.1V, typical 2100mAh; min. 2040mAh) x 2 | | |
| | | | |
| | LifeSupport™ battery swappable technology | | |
| | Optional: High capacity Li-ion battery (14.4V, typical | | |



GLACIER COMPUTER

603.882.1560. ext 6 sales@glaciercomputer.com https://glaciercomputer.com



| Dimension (W x D x H) & Weight | Tablet 329.5 x 238 x 24mm (12.97" x 9.37" x 0.94") 1.7kg (3.75lbs) ^{viii} | | | |
|--------------------------------|---|--|--|--|
| | Tablet + Optional keyboard dock: 340.5 x 307.5 x 47mm (13.40" x 12.10" x 1.85") 3.13kg (6.9lbs) ^{viii} | | | |
| Rugged Features | MIL-STD-810H certified IP66 certified MIL-STD-461G certified ^{ix} Vibration & 6ft (1.8m) drop-resistant ^x Optional: ANSI/UL 121201, CSA C22.2 NO. 213 (Class I, Division 2, Groups A, B, C, D) ^{xi} | | | |
| Environmental Specifications | Temperature ^{xii} : - Operating: -29°C to 63°C / -20°F to 145°F - Storage: -51°C to 71°C / -60°F to 160°F Humidity: - 95% RH, non-condensing | | | |
| Pre-installed software | Getac Utility Getac Camera Getac Geolocation Getac Barcode Manager ^{xiii} Optional: Absolute Persistence [®] | | | |
| Optional software | Getac Driving Safety Utility Getac KeyWedge Barcode Reader Utility Getac Device Monitoring System (GDMS) ^{xvi} Getac VGPS Utility ^{xvii} | | | |



Accessories

Battery (11.1V, typical 2100mAh; min. 2040mAh) AC adapter (90W, 100-240VAC) Capacitive stylus with tether

Optional:

Carry bag Battery (11.1V, typical 2100mAh; min. 2040mAh) High capacity Li-ion battery (14.4V, typical 3450mAh; min. 3300mAh) Multi-Bay charger (Dual-Bay) Multi-Bay charger (Eight-Bay) AC adapter (90W, 100-240VAC) Office dock AC adapter (120W, 100-240VAC) MIL-STD-461 AC adapter (90W, 100-240VAC) DC-DC vehicle adapter (120W, 11-32VDC) Digitizer pen Capacitive stylus with tether Protection film Hard handle Rotating hand strap with kickstand Shoulder strap (2-point) Shoulder harness (4-point; handsfree) Detachable keyboard Vehicle cradle xviii Keyboard dock Vehicle dock xiv, xviii Office dock Spare SSD kit 100W Type-C adapter Getac rugged keyboard

Bumper-to-Bumper Warranty

Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime. That is why Getac has introduced accidental damage as

standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs.

Bumper-to-Bumper is your hassle-free guarantee. That means you can depend on us to have your unit back in service within days.

Standard

3 years Bumper-to-Bumper

- I. FHD webcam and optional Windows Hello face-authentication camera (front-facing) are mutually exclusive options.
- II. Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
- III. Dedicated GPS is mutually exclusive with 4G LTE mobile broadband. Supports GPS and Glonass.
- IV. Units with 4G LTE option comes with an embedded SIM card slot. .
- V. 13.56MHz HF RFID/NFC reader (ISO 15693, 14443 A/B, Mifare and FeliCa™ compliant).
- VI. LF/HF RFID reader option is not Energy Star 8.0 compliant.
- VII. Smart card reader, HF RFID reader and Fingerprint scanner are mutually exclusive options.
- VIII. Weight and dimensions vary from configurations and optional accessories; optional high capacity batteries add approx. 11mm (H), 0.20kg.
- IX. MIL-STD-461 90W AC adapter sold separately.

- X. Drop test results vary from configurations and optional accessories.
- XI. Available with limited configurations and environment conditions.
- XII. Tested by an independent third-party test lab following MIL-STD-810H.
- XIII. Available when barcode reader option is selected.
- XIV. Available for laptop and tablet mode.
- XV. Units equipped with dual channel memory come with Intel® Iris® Xe Graphics.
- XVI. Only compatible with Windows 10.
- XVII. Models require either embedded or standalone GPS module.
- XVIII. Gamber Johnson and Havis vehicle docks are e-mark certified.

Information provided herewith is for reference only, available specification shall be subjected to quotation by request.

| | Vehicle Dock for Tablet Mode | Vehicle Dock for Laptop Mode | Office Dock for Tablet Mode | Office Dock for Laptop Mode |
|-------------------------|------------------------------------|------------------------------------|-------------------------------------|-------------------------------------|
| Serial Port | 1 | 1 | 1 | 1 |
| VGA | 1 | 1 | 1 | 1 |
| Microphone | - | - | 1 | 1 |
| Audio Output | - | - | 1 | 1 |
| DC in Jack | 1 | 1 | 1 | 1 |
| USB | USB 2.0 x 3 USB 3.2 Gen 1 x 3 | USB 2.0 x 3 USB 3.2 Gen 1 x 3 | USB 2.0 x 2 USB 3.2 Gen 1 x 3 | USB 2.0 x 2 USB 3.2 Gen 1 x 3 |
| LAN | 2 | 2 | 2 | 2 |
| HDMI 2.0 | 1 | 1 | 1 | 1 |
| RF Antenna Connector | 3 (WWAN, WLAN, GPS) | 3 (WWAN, WLAN, GPS) | - | - |
| Kensington Lock | 1 | 1 | 1 | 1 |

GETAC TECHNOLOGY CORPORATION

Via Paracelso 26, Centro Direzionale Colleoni,

Palazzo Cassiopea 3 20864 Agrate Brianza (MB)

Tel: +39 039 8901584

Sales-getac-Italy@getac.com I www.getac.com/it/

Copyright © 2022 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved. Le informazioni riportate sono puramente indicative,

Le specifiche disponibili sono da verificare al momento dell'offerta.



GLACIER COMPUTER 603.882.1560. ext 6 sales@glaciercomputer.com https://glaciercomputer.com

