



T800 FULLY RUGGED TABLET

- 8.1" HD LumiBond® display for better viewing experience
- Getac proprietary SnapBack add-on featuring smart card and contactless RFID reader combo or 2nd expanded battery
- Choice of 1D/2D imager barcode reader, Serial port and LAN port (RJ45)
- MIL-STD-810H and IP65 certified
- Enhanced enterprise security with TPM2.0, Windows disk encryption





GLACIER COMPUTER 603.882.1560. ext 6 sales@glaciercomputer.com https://glaciercomputer.com

T800 FULLY RUGGED TABLET



SPECIFICATIONS

Operating System	Windows 10 Pro
Mobile Computing Platform	Intel [®] Atom Processor x7-Z8750 1.6GHz, burst up to 2.56GHz
	- 2MB Cache
VGA Controller	Intel [®] HD Graphics
Display	8.1" IPS TFT LCD WXGA (1280 x 800)
	Protection film
	600 nits LumiBond [®] display with Getac sunlight readable technology
Storage & Memory	4GB LPDDR3
	Optional: 8GB LPDDR3
	128GB eMMC
	Optional: 256GB eMMC
Keyboard	Power button
	5 tablet programmable buttons
Pointing Device	Touchscreen
	- Capacitive multi-touch screen
	- Optional: Dual mode touchscreen (multi-touch and digitizer)
Expansion Slots	Optional: 1D/2D imager barcode reader, Serial port, Ethernet [†] Optional: SnapBack add-on: Smart card and HF RFID/NFC reader combo [#]
	Optional: SnapBack add-on: 2 nd expanded battery ⁱⁱ
	Optional: SnapBack add-on: Smart card and magnetic stripe reader "
I/O Interface	FHD webcam x 1
	8M pixels auto focus rear camera x 1
	Audio in/out combo x 1
	DC in Jack x 1
	USB 3.2 Gen 1 Type-A x 1
	Micro HDMI 1.4 x 1
	Docking connector x 1
	Optional: SIM card slot x 1 (Mini-SIM, 2FF) Optional: RF antenna pass-through for GPS, WWAN and
	WLAN



T800 FULLY RUGGED TABLET

Communication Interface	Intel® Wi-Fi 6 AX200, 802.11ax Bluetooth (v5.2) ^{IIII} Optional: Dedicated GPS Optional: 4G LTE mobile broadband ^{IVI} Optional: 10/100/1000 base-T Ethernet (Occupies expansion slot)
Security Features	TPM 2.0 Optional: SnapBack add-on: Smart card and HF RFID/NFC combo reader ^v Optional: SnapBack add-on: Smart card and magnetic stripe reader
Power	AC adapter (65W, 100-240VAC, 50/60Hz) Li-ion battery (7.4V, typical 4200mAh; min. 4080mAh) LifeSupport™ battery swappable technology (only with SnapBack 2 nd expanded battery)
Dimension (W x D x H) & Weight	227 x 151 x 24 mm (8.93" x 5.94" x 0.94") 0.88kg (1.94 lbs) ^{vi}
Rugged Features	MIL-STD-810H certified IP65 certified MIL-STD-461G certified Vibration & 6ft (1.8m) drop resistant ^{vii} Optional: ANSI/UL 121201, CSA C22.2 NO. 213 (Class I, Division 2, Groups A, B, C, D) ^{viii}
Environmental Specifications	Temperature ^{ix} : - Operating: -21°C to 50°C / -6°F to 122°F - Storage: -51°C to 71°C / -60°F to 160°F Humidity: - 95% RH , non-condensing
Pre-installed software	Getac Utility Getac Camera Getac Barcode Manager [×] Optional: Absolute Persistence [®]
Optional software	Getac Driving Safety Utility Getac KeyWedge Barcode Reader Utility Getac Device Monitoring System (GDMS) Getac VGPS Utility ^{xi}



T800 FULLY RUGGED TABLET

Accessories

Battery (7.4V, typical 4200mAh; min. 4080mAh) AC adapter (65W, 100-240VAC) Capacitive stylus with tether

Optional:

Carry bag Battery (7.4V, typical 4200mAh; min. 4080mAh) 2nd expanded battery (14.4V, 2100mAh) Multi-Bay charger (Dual-Bay) Multi-Bay expanded battery dock with adapter (Six-Bay) Multi-Bay charger (Eight-Bay) AC adapter (65W, 100-240VAC) Office dock AC adapter (90W, 100-240VAC) MIL-STD-461 AC adapter (90W, 100-240VAC) DC-DC vehicle adapter (120W, 11-32VDC) Digitizer pen Capacitive stylus with tether Protection film Hand strap Shoulder strap (2-point) Wrist strap Vehicle cradle xii Vehicle dock xii Office dock

Bumper-to-Bumper warranty

Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime.

That is why Getac has introduced accidental damage as standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs.

Bumper-to-Bumper is your hassle-free guarantee. That means you can depend on us to have your unit back in service within days.

Standard

3 years Bumper-to-Bumper

- I. 1D/2D imager barcode reader, Serial port, and Ethernet, are mutually exclusive options.
- II. All snapBack add-ons are mutually exclusive options.
- III. Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
- IV. Units with 4G LTE option comes with an embedded SIM card slot.
- V. 13.56MHz HF RFID/NFC reader (ISO 15693, 14443 A/B, Mifare and FeliCa™ compliant).
- VI. Weight and dimensions vary from configurations and optional accessories.
- VII. Drop test results vary from configurations and optional accessories.
- VIII. Available with limited configurations and environment coditions.
- IX. Tested by an independent third-party test lab following MIL-STD-810H.
- X. Available when barcode reader option is selected.
- XI. Models require either embedded or standalone GPS module.
- XII. Havis vehicle dock is e-mark certified.

Information provided herewith is for reference only, available specification shall be subjected to quotation by request.



GLACIER COMPUTER 603.882.1560. ext 6 sales@glaciercomputer.com https://glaciercomputer.com

