



Model	DT362Q	DT380Q	DT301Q	DT311Q	DT313Q
<b>System</b>					
<b>CPU</b>	Qualcomm Octa-Core, 2.0GHz	Qualcomm Octa-Core, 2.0GHz	Qualcomm Octa-Core, 2.0GHz	Qualcomm Octa-Core, 2.0GHz	Qualcomm Octa-Core, 2.0GHz
<b>RAM</b>	4GB	4GB	4GB	4GB	4GB
<b>Storage</b>	64GB Flash	64GB Flash	64GB Flash	64GB Flash	64GB Flash
<b>Operating System</b>	Android 9.0 and 10	Android 9.0 and 10			
<b>Display</b>	6" LED-backlight capacitive touch screen	8" LED-backlight, high-brightness (850 nits) capacitive touch screen	10.1" LED-backlight, high-brightness (1000 nits) capacitive touch screen	11.6" LED-backlight, high-brightness (1000 nits) capacitive touch screen	13.3" LED-backlight, high-brightness (1000 nits) capacitive touch screen
<b>Display Resolution</b>	720 x 1440	1920 x 1200	1920 x 1200	1920 x 1200	1920 x 1080
<b>Back Camera</b>	8 megapixel back camera	8 megapixel back camera	8 megapixel back camera	8 megapixel back camera	8 megapixel back camera
<b>Control Switch and Buttons</b>	1 power button, 2 trigger buttons	1 power button, 1 trigger button	1 power button, 2 brightness control buttons, 5 programmable buttons	1 power button, 2 brightness control buttons, 5 programmable buttons	1 power button, 2 brightness control buttons, 5 programmable buttons

## Network Interface

<b>WLAN</b>					
<b>Bluetooth</b>	Bluetooth 4.1 LE	Bluetooth 4.1 LE	Bluetooth 4.1 LE	Bluetooth 4.1 LE	Bluetooth 4.1 LE

## I/O Ports

<b>USB Port</b>	USB Type-C x 1 (data transmitting and charging)	USB 3.0 X 1	USB 3.0 x 1, USB Type C x 1 (data transmitting and charging)	USB 2.0 x 1, USB 3.0 x 1, USB Type C x 1 (data transmitting and charging)	USB 3.0 x 3, USB Type-C x 1 (data transmitting and charging)
<b>Headset Jack</b>	N/A	1 (3.5mm)	1 (3.5mm)	1 (3.5mm)	1 (3.5mm)
<b>DC-in</b>	N/A	1	N/A	N/A	N/A
<b>Ethernet</b>	N/A	N/A	1	1	1
<b>SD Slot</b>	1 micro SD card slot	1 micro SD card slot	1 micro SD card slot	1 micro SD card slot	1 micro SD card slot

## Mechanical and Environmental

<b>AC/DC Adapter</b>	Input: 100-240V AC; Output: 20V DC, 3.25A	Input: 100-240V AC; Output: 12V DC, 5A	Input: 100-240V AC; Output: 20V DC, 3.25A		
<b>Battery Pack</b>	Hot swappable battery, 4200mAh	Hot swappable battery, 3.7V, 8800mAh	Hot swappable battery, 7.6V, 6000mAh		
<b>Enclosure</b>	ABS + PC plastics		ABS + PC plastics and magnesium-aluminum alloy		
<b>Dimensions (H x W x D)</b>	7.34 x 3.39 x 0.96 in/ 186.4 x 86.2 x 24.5 mm	5.7 x 8.3 x 0.8 in/ 145.4 x 210 x 20.4 mm	7.8 x 11 x 0.86 in/ 198 x 280 x 21.9 mm	8.3 x 12.4 x 0.86 in/ 212 x 316 x 21.9 mm	10.6 x 13.2 x 0.8 in/ 270 x 335 x 21 mm
<b>Weight</b>	1.1 lbs/ 480 g	1.99 lbs/ 900 g	2.86 lbs/ 1.3 kg	3.5 lbs/ 1.6 kg	3.97 lbs/ 1.8 kg
<b>Durability</b>	IP65 and MIL-STD-810G certified		IP65 and MIL-STD-810G certified		IP65 and MIL-STD-810G certified
<b>Regulatory</b>	FCC Class B, RoHS compliant		FCC Class B, CE, RoHS compliant		
<b>Temperature</b>	Operation: -10°C to 50°C (14°F to 122°F) Storage: -20°C to 60°C (-4°F to 140°F)	Operation: 0°C to 50°C (32°F to 122°F) Storage: -20°C to 60°C (-4°F to 140°F)	Operation: -10°C to 50°C (-14°F to 122°F) Storage: -55°C to 70°C (-67°F to 158°F)		
<b>Humidity</b>	0% – 90% non-condensing				

## Major Options

<b>Front Camera</b>	N/A	N/A	2 megapixel front camera		
<b>Magnetic Stripe Reader</b>	N/A	N/A	N/A	N/A	N/A
<b>Barcode Scanner (2D)</b>	2D barcode scanner; reads 1D also				
<b>GPS</b>	Yes	Yes	Yes	Yes	Yes
<b>NFC/RFID Reader</b>	HF 13.56MHz, ISO standard 15693, 14443A(B) & 18000-3 mode-1	N/A	HF 13.56MHz, ISO standard 15693, 14443A(B) & 18000-3 mode-1		N/A
<b>Mobile Broadband</b>	4G LTE/AWS	4G LTE/AWS	4G LTE/AWS	4G LTE/AWS	4G LTE/AWS

\* Specifications subject to change without notice.



**Glacier Computer**  
603.882.1560 Ext. 6  
[sales@glaciercomputer.com](mailto:sales@glaciercomputer.com)  
[www.glaciercomputer.com](http://www.glaciercomputer.com)