



DT362GL Handheld Rugged Tablet

Slim, Rugged, Multi-functional Wireless Computing

The DT Research DT362GL Handheld Rugged Tablet features the integration of a brilliant 6" capacitive touchscreen and a high performance yet energy efficient processor within a slim, lightweight, durable package. With built-in Wi-Fi and a smart card reader, as well as optional back camera barcode scanner, GNSS, NFC, and UHF RFID reader, this robust tablet offers seamless information capture and transmission for improved workflow. Rated IP65, MIL-STD-810G and optional C1D2, the DT362GL Handheld Rugged Tablet provides reliable operation in harsh, mission-critical environments.



Features

- 6" LED-backlit touchscreen, digital pen support
- Intel® Pentium® Silver 4-core processor
- Microsoft® Windows® 10/11 IoT Enterprise operating system
- NIST compliant BIOS available
- IP65-rated for water and dust resistance
- MIL-STD-810G for shock and vibration protection
- Hot-swappable battery pack
- Built-in smart card/CAC reader

Major Options

- NFC or UHF RFID reader
- Back camera
- Barcode scanner
- GPS module
- C1D2 Groups A, B, C and D

Specifications

System

CPU	Intel® Pentium® Silver 4-Core, 1.10 GHz (up to 2.70 GHz)
RAM	8GB
Storage	256GB flash
Operating System	Microsoft® Windows® 10/11 IoT Enterprise
NIST Compliance	NIST Compliant BIOS Available
Display	6" LED-backlit (350 nits) touchscreen
Display Resolution	720 x 1440
Control Switch and Buttons	1 Power Button, 2 Trigger Buttons

Network Interface

WLAN	Wi-Fi 802.11ac, 2.4/5 GHz Dual Band
-------------	-------------------------------------

I/O Ports

USB Port	USB Type-C x 1 (data transmitting and charging; data transmitting only available in one insertion direction)
Smart Card/CAC Reader	Full Slot (Reads ISO 7816 T=0, T=1); 1.8/3/5V Smart Card

Mechanical and Environmental

AC/DC Adapter	Input: 100-240V AC; Output: 20V DC, 3.25A
Battery Pack	Hot-Swappable Battery (3300mAh)
Enclosure	ABS + PC Plastic
Dimensions (H x W x D)	7.6 x 3.7 x 1.2 in/192 x 95 x 31 mm
Weight	1.1 lbs/485 g
Durability	IP65 and MIL-STD-810G Class 1, Division 2, Groups A, B, C and D (Optional)
Regulatory	FCC Class B, RoHS Compliant
Temperature	Operation: 14°F to 122°F (-10°C to 50°C); Storage: -4°F to 140°F (-20°C to 60°C)
Humidity	0% – 90% Non-Condensing

* Specifications subject to change without notice.

Major Options

Barcode Scanner	2D Barcode Scanner (Reads 1D & 2D)
Camera	8 MP Back Camera
NFC/RFID Reader	HF 13.56 MHz, ISO 15693, 14443A(B) & 18000-3 Mode 1
UHF RFID Reader	865 – 928MHz, EPCglobal Class 1 Gen 2/ ISO 18000-6C; Reading Distance of 16 ft (4.87m) with the Built-In ThingMagic micro Module & Embedded Antenna; Reading Distance of 30 ft (9.1m) with Trigger Grip
GNSS Module	GPS Module with Concurrent Reception of GPS & GLONASS; Industry-Leading - 167 dBm Navigation Sensitivity

Accessories

- Digital Pen



- Desktop Charging Cradle



- 4-Bay System Gang Charger



- Battery Pack



- Trigger Grip for UHF RFID Reader; 30 feet UHF RFID Reader read distance



- Charging Cradle for UHF RFID Reader Trigger Grip



- Charging Cradle for Trigger Grip



- Trigger Grip for Barcode Scanner

