


UROVO



Enterprise Mobile Computer DT50

- Octa-core 2.45GHz processor and Android 13 operating system, enable seamless operation of multiple applications.
- Wi-Fi 6 ready(802.11ax ready), offers faster transmission speed, lower latency, and enhanced security.
- Advanced Scan Engine, features dual lens architecture and fast, near and far switching mechanism, with a read range from 6 cm to 10 m.
- 13 MP rear camera with PDAF technology, captures clear images within milliseconds.
- Large 5.7-inch full display, high sensitivity and ultra-brightness.
- With a high-capacity 5000mAh battery, this device offers long-lasting endurance.



Charging Cradle



Scanning
Pistol Grip



Hand Strap



Protective Cover



Glass
Screen Protector



RFID Sled



4 Batteries
Charge Cradle



Multi-Charge Cradle




DT50 Enterprise Mobile Computer

Specifications


UROVO


 **Processor**
Octa-core 2.45GHz


 **O.S.**
Android 13


 **Memory**
RAM: 4GB ROM: 64GB
RAM: 6GB ROM: 64GB (optional)
Micro-SD card, Up to 256 GB


 **Display**
5.7 inch display,
720*1440

 **Touch Screen**
Ultra sensitive capacitive touch panel
Support multi-touch
Works with gloves and wet fingers


 **Dimensions**
Dimensions: 162.6*76*13.6mm
Weight: 265g


 **Scanning**
Professional scan engine;
Support international
standard 1D/2D barcode;
Support barcode displayed
on screen and colored barcode


 **Audio**
Dual-Microphone
(noise cancellation),
Speaker(1.5W),
Receiver, 3.5mm audio jack

 **Main battery**
Capacity: 3.85V 5000mAh


 **Camera**
Front 5MP, Rear 13MP
with flash


 **Buttons**
PWR button
Vol+/- button
Scan button*2
Custom button

 **Slots**
Micro SD/TFx1
Nano- SIMx2

 **Connections**
4G, 3G, 2G
Bluetooth: BT 5.0+BR/EDR+BLE
Wi-Fi: 2.4G/5G, IEEE 802.11a/b/
g/n/ac/d/e/h/i/k/r/v/w
Support 802.11ax ready

 **Positioning**
GPS
A-GPS
BeiDou
GLONASS
Galileo

 **Protection**
IP67
1.5m drop resistance

 **Environment**
Operating Temp.: -20 ~ +60°C
Storage Temp.: -40 ~ +70°C
Humidity: 5%RH ~ 95%RH(No condensation)
ESD: +/-15kv Air; +/-8kv contact

Urovo Technology Co., Ltd.

- Tel: 86 755-22673926
- Website: en.urovo.com
- E-mail: urovo@urovo.com
- Address: Room 613,6/F.,Asia Trade Centre,79 Lei Muk Road,Kwai Chung,N.T.,Hong Kong



Glacier Computer

603.882.1560 Ext. 6

sales@glaciercomputer.com

www.glaciercomputer.com