



R10 Tablet

VERSATILITY REDEFINED, INTELLIGENCE AMPLIFIED.

- 10.1" LCD DynaVue® SR display with 1000 nits and capacitive touchscreen
- Intel® Core™ Ultra processor with integrated NPU AI up to 48 TOPS
- Copilot+ PC with enhanced security including 5MP Windows Hello camera and Intel® vPro®
- Wireless dual SIM 4G LTE/5G, Wi-Fi 7 and Bluetooth® V5.4
- Flexible battery options, including high-capacity and hot-swappable bridge battery
- Versatile I/Os configurations including Thunderbolt™ 4 and optional RFID, barcode & smart card reader



DURABILITY	<ul style="list-style-type: none"> MIL-STD-810H certified (Drop, Shock, Vibration, Rain, Dust, Altitude, Freeze/Thaw, High/Low Temperature, Temperature Shock, Humidity, Explosive Atmosphere, Salt Fog) MIL-STD-461G certified (Conduction, Radiation, Conducted Susceptibility, Radiated Susceptibility) Optional ANSI/UL 121201, Class I, Division 2 6' drop 26 faces IP 66 certified Magnesium alloy chassis Port covers Sunlight readable display Optional swappable battery technology
-------------------	---

OPERATING SYSTEM	Windows® 11 Pro 64-bit
-------------------------	------------------------

PROCESSORS	<ul style="list-style-type: none"> Intel® Core™ Ultra 7 268V vPro Enterprise (32GB RAM, 12MB Cache, up to 5.0 GHz, 8 cores, 8 threads, with Intel® AI Boost NPU up to 48 TOPS) Intel® Core™ Ultra 7 266V vPro Enterprise (16GB RAM, 12MB Cache, up to 5.0 GHz, 8 cores, 8 threads, with Intel® AI Boost NPU up to 48 TOPS) Intel® Core™ Ultra 7 258V (32GB RAM, 12MB Cache, up to 4.8 GHz, 8 cores, 8 threads, with Intel® AI Boost NPU up to 48 TOPS) Intel® Core™ Ultra 7 256V (16GB RAM, 12MB Cache, up to 4.8 GHz, 8 cores, 8 threads, with Intel® AI Boost NPU up to 48 TOPS) Intel® Core™ Ultra 5 238V vPro Enterprise (32GB RAM, 8MB Cache, up to 4.7 GHz, 8 cores, 8 threads, with Intel® AI Boost NPU up to 40 TOPS) Intel® Core™ Ultra 5 236V vPro Enterprise (16GB RAM, 8MB Cache, up to 4.7 GHz, 8 cores, 8 threads, with Intel® AI Boost NPU up to 40 TOPS) Intel® Core™ Ultra 5 228V (32GB RAM, 8MB Cache, up to 4.5 GHz, 8 cores, 8 threads, with Intel® AI Boost NPU up to 40 TOPS) Intel® Core™ Ultra 5 226V (16GB RAM, 8MB Cache, up to 4.5 GHz, 8 cores, 8 threads, with Intel® AI Boost NPU up to 40 TOPS)
-------------------	--

GRAPHICS	Intel® Arc™ 140V GPU (for Intel® Core™ Ultra 7 CPU) Intel® Arc™ 130V GPU (for Intel® Core™ Ultra 5 CPU)
-----------------	--

MEMORY	16GB up to 32GB on Package (LPDDR5X)
---------------	--------------------------------------

STORAGE	256GB NVMe PCIe SSD <ul style="list-style-type: none"> Optional 512GB/1TB/2TB NVMe PCIe SSD Optional OPAL 2.0 SSD
----------------	--

DISPLAY	10.1" TFT LCD WUXGA (1920 x 1200) <ul style="list-style-type: none"> 1000 nits DynaVue® sunlight readable display with capacitive multi-touch screen Optional with digitizer User selectable touch mode for Finger/Water, Glove, or Stylus programmable function Support Microsoft Pen Protocol (MPP) 1.51 active pen function
----------------	---

AUDIO	<ul style="list-style-type: none"> Integrated microphone x 2 Intel® High Definition Audio Compliant Integrated speaker x 1 Keyboard volume and mute controls
--------------	--

CAMERA	<ul style="list-style-type: none"> Integrated 5.0 MP IR camera for Windows Hello with dynamic shutter design Integrated 11.0 MP rear auto-focus camera with flash and dynamic shutter design
---------------	--

KEYBOARD & INPUT	7 buttons (4 user-definable keys)
COMMUNICATIONS	<ul style="list-style-type: none"> Integrated 10/100/1000 Ethernet Intel® Wi-Fi 7 BE201 (802.11 be) Bluetooth® V5.4 Optional dedicated GPS module (UBLOX-NEO-M9N)¹ Optional 4G LTE multi-carrier mobile broadband with integrated GPS¹ Optional 5G with integrated GPS¹ Optional RF antenna pass-through for GPS, WWAN, and WLAN

SECURITY	<ul style="list-style-type: none"> Intel® vPro® Technology (per CPU options) Secured-core PC TPM 2.0 NIST BIOS compliant IR Camera (Support Windows Hello) Stealth mode Kensington lock Night vision mode Optional fingerprint scanner² Optional smart card reader⁴ Optional LF/HF-RFID (NFC) reader⁴ Optional UHF-RFID (NFC) reader^{2, 4}
-----------------	--

I/O INTERFACES	<ul style="list-style-type: none"> Thunderbolt 4 (type C) x 1 USB 3.2 Gen2 (type A) x 1 microSD card (microSDXC) x 1 10/100/1000 Ethernet (RJ45) x 1 Docking connector (20-pin Pogo) x 1 Dual SIM (Nano SIM & eSIM) Audio in/out (combo jack) x 1 DC-In jack x 1 Optional USB 3.2 Gen 1 (type C) x 1³ Optional USB 3.2 Gen 1 (type A) x 1³ Optional serial port (RS232, 422 and 485 : D-sub,9-pin) x 1³ Optional 1D/2D barcode reader x 1³ Optional 2nd 10/100/1000 Ethernet (RJ45) x 1³ Optional smart card reader x 1⁴ Optional RF antenna pass-through for GPS, WWAN and WLAN
-----------------------	---

EXPANSION SLOT	<ul style="list-style-type: none"> Optional magnetic stripe reader Optional smart card reader⁴ Optional smart card reader with LF/HF-RFID (NFC)⁴ Optional LF/HF-RFID (NFC) reader⁴ Optional UHF-RFID (NFC) reader^{2, 4}
-----------------------	--

POWER	AC adapter: 100-240V, 50Hz-60Hz, 65W Main battery: Li-Ion, 11.4V, 4400mAh, 8.5 hours ⁵ <ul style="list-style-type: none"> Optional hi-cap battery Li-Ion 11.4V, 8700mAh, 17 hours⁵ Optional bridge battery: 1 minute swap time⁶
--------------	--

ENVIRONMENT	<ul style="list-style-type: none"> Temperature Operating : -29°C ~ 63°C / - 20°F ~ 145°F Storage : -51°C ~ 71°C / -60°F ~ 160°F Humidity : 5% ~ 95%
--------------------	---

DIMENSION & WEIGHT	<ul style="list-style-type: none"> 10.43" (W) x 7.46" (D) x 0.83" (H) 2.65 lbs
-------------------------------	--

WARRANTY	3-Year Accidental Damage Warranty
-----------------	-----------------------------------

- Dedicated GPS, 4G LTE and 5G are mutually exclusive options.
- Fingerprint scanner and UHF-RFID (NFC) are mutually exclusive options.
- Mutually exclusive options.
- Mutually exclusive options.
- Tested using the MobileMark 2014 battery life benchmark. Results may vary under different situations including hardware configuration, software, operating conditions, power management settings and other factors.
- The system will stay operating within 60 seconds when user swaps the battery.

