


## B360 Pro FULLY RUGGED LAPTOP



- AI-ready with the latest Intel® Core™ Ultra Processors (Series 2) and Intel® AI Boost technology
- Optional NVIDIA® Quadro® RTX A500 4GB discrete graphic controller
- MIL-STD 810H, 6ft operating drop rating, IP66 certified, and optional salt fog resistant
- 13.3" FHD LumiBond display with Getac sunlight readable technology (1,400 nits) and capacitive touchscreen
- Enhanced enterprise security with optional dual user replaceable storage, Windows Hello face-authentication camera, integrated 1D/2D imager barcode reader and multi-factor authentication options
- LifeSupport battery swappable technology



# SPECIFICATIONS

## Generation

G3

## Operating System

Windows 11 Pro

## Mobile Computing Platform

Intel® Core™ Ultra 5 processor 225H  
Max. 4.9GHz with Intel® Turbo Boost Technology  
- 18MB Intel® Smart Cache

## Platform options:

Intel® Core™ Ultra 5 processor 235H, vPro® Enterprise  
Max. 5.0GHz with Intel® Turbo Boost Technology  
- 18MB Intel® Smart Cache

Intel® Core™ Ultra 7 processor 255H

Max. 5.1GHz with Intel® Turbo Boost Technology  
- 24MB Intel® Smart Cache

Intel® Core™ Ultra 7 processor 265H, vPro® Enterprise

Max. 5.3GHz with Intel® Turbo Boost Technology  
- 24MB Intel® Smart Cache

## Graphics

Intel® Arc™ Graphics 1

Optional: NVIDIA® Quadro®  
RTX A500 4GB discrete graphic controller <sup>ii,iii</sup>

## NPU

Intel® AI Boost

## Display

13.3" Wide Viewing Angle TFT LCD FHD (1920 x 1080)  
Protection film

1,400 nits LumiBond display with  
Getac sunlight readable technology  
Capacitive multi-touch screen

## Storage & Memory

16GB DDR5

Optional: 32GB / 64GB DDR5

256GB PCIe NVMe SSD

Optional: 512GB / 1TB / 2TB PCIe NVMe SSD

Optional 2<sup>nd</sup> storage <sup>iv</sup>:

256GB / 512GB / 1TB / 2TB PCIe NVMe SSD  
Optional multimedia bay storage : 1TB / 2TB SATA SSD

## Keyboard

LED backlit membrane keyboard

## Pointing Device

Touchscreen

- Capacitive multi-touch screen

Touchpad

- Touchpad with two buttons

## Audio

Integrated stereo speakers

Integrated dual-array microphone

## Expansion Slot

Smart card reader x 1

Optional: Micro SD card reader x 1

Optional: Discrete graphics controller, or PCMCIA Type II,  
or ExpressCard 54

Optional: 1D/2D imager barcode reader

## Multimedia Bay

Configurable options <sup>v,vi</sup> :

1. Optional: DVD super multi drive, or Blu-Ray super multi drive,  
or 3<sup>rd</sup> storage

2. Optional: 3<sup>rd</sup> battery

## I/O Interface

5MP webcam x 1 <sup>vii</sup>

Audio in/out combo x 1

DC in Jack x 1

PowerShare USB 3.2 x 1

USB 3.2 Gen 2 Type-A x 1

Thunderbolt™ 4 Type-C x 1 <sup>viii</sup>

LAN (RJ45) x 1

HDMI 2.0 x 1

Docking connector x 1

Optional: SIM card slot x 1 (Mini-SIM, 2FF) <sup>ix</sup>

Optional: Windows Hello face-authentication

SMP camera (front-facing) x 1 <sup>x</sup>

Optional: RF antenna pass-through for GPS, WWAN and WLAN

## Configurable I/O options <sup>x</sup>:

1. Serial port (9-pin; D-sub) x 1 + External VGA (15-pin; D-sub) x 1

2. Serial port (9-pin; D-sub) x 1 + Display port x 1

3. Serial port (9-pin; D-sub) x 1 + External VGA (15-pin; D-sub) x 1

+ 2<sup>nd</sup> LAN (RJ45) x 1

4. Serial port (9-pin; D-sub) x 1 + Display port x 1 + 2<sup>nd</sup> LAN (RJ45) x 1

5. Serial port (9-pin; D-sub) x 1 + 2<sup>nd</sup> Thunderbolt™ 4 Type-C x 1

6. Serial port (9-pin; D-sub) x 1 + 2<sup>nd</sup> Thunderbolt™ 4 Type-C x 1

+ 2<sup>nd</sup> LAN (RJ45) x 1

7. Serial port (9-pin; D-sub) x 2 + External VGA (15-pin; D-sub) x 1

8. Serial port (9-pin; D-sub) x 2 + Display port x 1

9. Serial port (9-pin; D-sub) x 2 + External VGA (15-pin; D-sub) x 1

+ 2<sup>nd</sup> LAN (RJ45) x 1

10. Serial port (9-pin; D-sub) x 2 + Display port x 1 + 2<sup>nd</sup> LAN (RJ45) x 1

11. Serial port (9-pin; D-sub) x 2 + 2<sup>nd</sup> Thunderbolt™ 4 Type-C x 1

12. Serial port (9-pin; D-sub) x 2 + 2<sup>nd</sup> Thunderbolt™ 4 Type-C x 1

+ 2<sup>nd</sup> LAN (RJ45) x 1

## Communication Interface

10/100/1000 base-T Ethernet

Intel® Wi-Fi 7 BE200, 802.11be

Bluetooth (v5.4) <sup>xi</sup>

Optional: Dedicated GPS with L1/L5 <sup>xii</sup>

Optional: 4G LTE mobile broadband with integrated GPS <sup>xiii, xiv, xv</sup>

Optional: 5G Sub-6 with integrated GPS <sup>xvi, xvii, xviii</sup>

Optional: Dual SIM (Mini-SIM 2FF and e-SIM) <sup>ix, xv</sup>

	Vehicle Dock	Office Dock
Serial Port	1	1
External VGA	1	1
Microphone	-	1
Audio Output	-	1
DC in Jack	1	1
USB	6	5
LAN	2	2
HDMI 1.3	1	1
RF Antenna Connector	3 (WWAN, WLAN, GPS)	-

## Security Feature

TPM 2.0

Kensington lock

Smart card reader

Getac Disk Wipe

Optional: Fingerprint reader <sup>xv</sup>

Optional: HF RFID reader <sup>xvi, xvii</sup>

Optional: Absolute Persistence®

## Power

AC adapter (90W, 100-240VAC, 50/60Hz)

AC adapter (120W, 100-240VAC, 50/60Hz) <sup>ii</sup>

High capacity Li-ion battery (10.8V, typical 6900mAh; min. 6600mAh) x 2

Optional: Multimedia bay battery (11.1V, typical 4200mAh; min. 2080mAh) x 1

LifeSupport battery swappable technology

## Dimension (W x D x H) & Weight

342 x 281 x 53.5mm (13.46" x 11.06" x 2.11")

3.08kg (6.79lbs) <sup>xviii</sup>

## Rugged Feature

MIL-STD-810H certified

IP66 certified

MIL-STD-461G certified <sup>xix</sup>

Vibration & 6ft (1.8m) drop resistant

Optional: ANSII/UL 121201, CSA C22.2 NO. 213

(Class I, Division 2, Groups A, B, C, D) <sup>xx</sup>

Optional: Salt fog certified

## Environmental Specification

Temperature <sup>xxi</sup>

- Operating: -29°C to 63°C / -20°F to 145°F <sup>xxii</sup>

- Storage: -51°C to 71°C / -60°F to 160°F

Humidity:

- 95% RH, non-condensing

## Pre-installed Software

Getac Utility

Getac Geolocation

Getac Barcode Manager <sup>xxiii</sup>

Optional: Absolute Secure Endpoint

## Optional Software

Getac Driving Safety Utility

Getac VGPS Utility <sup>xxiv</sup>

Absolute Secure Access

## Accessories

High capacity Li-ion battery (10.8V, typical 6900mAh; min. 6600mAh)

AC adapter (90W, 100-240VAC)

Capacitive stylus with tether

## Optional:

Carry bag

High Capacity Li-ion Battery (10.8V, typical 6900mAh; min. 6600mAh)

Multi-Bay charger (Dual-Bay)

Multi-Bay charger (Eight-Bay)

AC adapter (90W, 100-240VAC) <sup>ii</sup>

AC adapter (120W, 100-240VAC) <sup>ii</sup>

MIL-STD-461 AC adapter (90W, 100-240VAC)

DC-DC vehicle adapter (120W, 11-32VDC)

Capacitive stylus with tether

Protection film

Vehicle cradle <sup>xxv</sup>

Vehicle dock <sup>xxvi</sup>

Office dock

Spare SSD kit

100W Type-C adapter <sup>xxvii</sup>

## Bumper-to-Bumper Warranty

Accidents can take your equipment out of service

when you least expect it, especially in a rugged

environment, which can cause costly equipment

downtime.

That is why Getac has introduced accidental

damage as standard under our

Bumper-to-Bumper warranty, to help minimize

your enterprise IT costs.

Bumper-to-Bumper is your hassle-free guarantee.

That means you can depend on us to have your

unit back in service within days.

## Standard

3 years Bumper-to-Bumper

# B360 Pro FULLY RUGGED LAPTOP

- I. Units equipped with 16GB and dual channel memory come with Intel® Arc™ Graphics.
- II. 120W AC adapter is used for office dock and for device configured with discrete graphics card.
- III. Discrete graphics card, PCMCIA slot, and ExpressCard slot are mutually exclusive.
- IV. Second storage is optional and will be fitted with a removable cover when not chosen at point of purchase.
- V. Option 1 and 2 are mutually exclusive.
- VI. Factory option. Not user swappable.
- VII. SMP webcam and optional Windows Hello face-authentication SMP camera (front-facing) are mutually exclusive options.
- VIII. The configuration with a discrete graphic controller does not support USB-C power delivery function.
- IX. Units with 4G/5G option come with an embedded SIM card slot.
- X. External VGA, Display port, and 2<sup>nd</sup> Thunderbolt™ 4 Type-C are mutually exclusive.
- XI. Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
- XII. Support GPS, GLONASS, Galileo, BeiDou and QZSS.
- XIII. Only available in the US, UK, EU, Australia, and New Zealand.
- XIV. One physical SIM card slot and one eSIM. Network service may vary depending on local telecommunication providers.
- XV. Fingerprint reader and HF RFID reader are mutually exclusive.
- XVI. HF (13.56MHz) combo HF RFID/NFC reader (iClass, HID Prox, ISO 15693, 14443 A/B, Mifare and FelICa™ compliant).
- XVII. Weight and dimensions vary from configurations and optional accessories.
- XVIII. MIL-STD-461 90W AC adapter sold separately.
- XIX. Available with limited configurations and environment conditions.
- XX. Tested by an independent third-party test lab following MIL-STD-810H.
- XXI. For optional DVD / Blu-Ray super-multi drive, the operating temperature is -10°C to 50°C / 14°F to 122°F.
- XXII. Available when barcode reader option is selected.
- XXIII. Models require either embedded or standalone GPS module.
- XXIV. Gamber Johnson and Havis vehicle docks are e-mark certified.
- XXV. Do not support the configurations with discrete graphics card.

Information provided herewith is for reference only, available specification shall be subjected to quotation by request.



**Call: 866.724.6257**

**EMAIL: SALES@GLACIERCOMPUTER.COM**

**VISIT: GLACIERCOMPUTER.COM**